



	RAC 420		RAC 630	
Electric Motor	380V	18,5 Kw / 25 HP	380V	22 Kw / 30 HP
Diesel Engine	Deutz F4L912	4 Cylinder 80 HP	Deutz F4L912	4 Cylinder 80 HP
	AFG Z - 108	2 Cylinder 35 HP	AFG D - 108	3 Cylinder 55 HP
Cooling System	Cooling Fan		Cooling Fan	
Filtration	Pre - air filter system		Pre - air filter system	
F.A.D. / Air Flow Capacity	7m³/min 420m³/hour	Free Air Delivery	10,5m³/min 6300m³/hour	Free Air Delivery
Pressure	2 bar		2 bar	
Piston Diameter	Ø 160 - Ø 160 - Ø 160		Ø 220 - Ø 220 - Ø 220	
Connection Type	Direct Coupling		Direct Coupling	
Dimension (mm)	1000 x 1500 x 1000		1000 x 1500 x 1000	
Weight	250kg Bare Compressor 450 kg with electric motor		280kg Bare Compressor 500 kg with electric motor	
	520kg with diesel engine		600kg with diesel engine	



- Simple and Strong Construction
- Fan Cage - Output pressure manometer
- Direct Coupling System
- Operates without vibration - Balanced
- Crank PTO type driven
- Spares are always available in stock
- Oil indicator High
- Quality cast iron cylinders
- Safety Valve
- Mechanic friction prevent system
- High efficiency cooling system
- Long Life filters design